



316 Stainless M10 Welded Boss Holderbats

| RSL CODE | SIZE | L | W x T | BOLT | NUT | REC LOAD |
|----------|---------------|-----|----------|---------|-----|----------------|
| MRS-021 | 15nb (21od) | 65 | 25 x 2.0 | M6 x 20 | - | 188kg (1.84kN) |
| MRS-027 | 20nb (27od) | 73 | 25 x 2.0 | M6 x 20 | - | 188kg (1.84kN) |
| MRS-034 | 25nb (34od) | 80 | 25 x 2.0 | M6 x 20 | - | 188kg (1.84kN) |
| MRS-043 | 32nb (43od) | 90 | 25 x 2.0 | M6 x 20 | - | 188kg (1.84kN) |
| MRS-048 | 40nb (48od) | 98 | 25 x 2.0 | M6 x 20 | - | 188kg (1.84kN) |
| MRS-060 | 50nb (60od) | 105 | 25 x 2.5 | M6 x 25 | - | 235kg (2.31kN) |
| MRS-076 | 65nb (76od) | 125 | 25 x 2.5 | M6 x 25 | - | 235kg (2.31kN) |
| MRS-089 | 80nb (89od) | 138 | 25 x 2.5 | M6 x 25 | - | 235kg (2.31kN) |
| MRS-101 | 101.6od | 150 | 25 x 2.5 | M6 x 25 | - | 235kg (2.31kN) |
| MRS-115 | 100nb (115od) | 165 | 25 x 3.0 | M8 x 30 | ✓ | 282kg (2.82kN) |
| MRS-140 | 125nb (140od) | 190 | 25 x 3.0 | M8 x 30 | ✓ | 282kg (2.82kN) |
| MRS-168 | 150nb (168od) | 225 | 25 x 3.0 | M8 x 30 | ✓ | 282kg (2.82kN) |

Note: Recommended maximum loads have a 2.5 safety factor.

Listed By 

Compliant to NZS4541:2013

